



## Canopy Assembly Instructions

These instructions are also available on the web at [www.captainchoicelifts.com](http://www.captainchoicelifts.com)

Canopy side rail length and the number of canopy bows will vary with the length of the Canopy. Position the canopy side rails and extension legs for canopy height adjustment to adequately cover your boat.

### Contents:

1. 2 Canopy Side Rails
2. Canopy Bows (Qty. varies based on length of canopy)
3. 2 - Canopy End Cap Bows
4. 4 - Canopy extension legs for height adjustment (4', 6', and 8' options)
5. 4 - 7' Long Leg uprights (attaches to front and rear beams of lift)
6. 1 - center strip
7. Bag - Full canopy assembly
  - A. 4 - 3/8" x 3 1/2" bolts
  - B. 4 - 3/8" x 3 1/4" bolts
  - C. 8 - 3/8" nylock nuts
  - D. 4 - 3/8" Flat Washers
  - E. 4 - "J" Brackets
  - F. 1/4" x 1 1/2" carriage bolts (Qty. varies based on length of canopy)
  - G. 1/4" nuts (Qty. varies based on length of canopy)

### Tools required:

1. 9/16" socket wrench or impact wrench
2. 7/16" box wrench, socket wrench or impact wrench
3. 9/16" box wrench

Assembly:

1. Insert canopy extension legs into leg uprights and bolt at desired height using:

A. 4 - 3/8" x 3 1/2" bolts

B. 4 - 3/8" nylock nuts



2. Attach canopy side rails to canopy extension legs using the hardware below. The flat side of "J" bracket should be on the outside of extension leg.

A. 4 - 3/8" x 3 1/4" bolts

B. 4 - 3/8" nylock nuts

C. 4 - 3/8" Flat Washers

D. 4 - "J" Brackets



**Outside of Lift**

3. Attach the canopy end cap bows and the canopy bows to the side rails by slipping them over the pegs as shown in the picture below. Make sure the tabs on the end cap are facing inward toward each other.



4. Attach the center strip to the top side and center of the canopy bows using:  
A. 1/4" x 1 1/2" carriage bolts (Qty. varies based on length of canopy)  
B. 1/4" nuts (Qty. varies based on length of canopy)



End Cap Tab



Middle Bows

This concludes the assembly instructions